




VELLUTO / ALGHERO

Rilasciato – Issued 22.05.2023

CHARACTERISTICS

COMPOSIZIONE <i>COMPOSITION</i>	90 % fibra acrilica per esterno tinta in massa – 10% PES 90% outdoor acrylic fibre solution dyed – 10% PES			
CARATTERISTICHE MECCANICO FISICHE PHYSICAL MECHANICAL PROPERTIES	UNITA' UNIT	TOLLERANZA TOLERANCE	VALORI VALUES	NORMATIVA SPECIFICATION
PESO TOTALE TOTAL WEIGHT	g/m2	+ 2%	500	
ALTEZZA WIDTH	cm	± 2%	140	
SOLIDITA' COLORI ALLA LUCE COLOUR FASTNESS TO LIGHT (XENOTEST)	Blue scale		7-8	UNI EN ISO 105-B04
PILLING PILLING	N		5	UNI EN ISO 12945-2
RESISTENZA ALL'ABRASIONE ABRASION RESISTANCE	Cicli / cycles		60.000	UNI EN ISO 12947-2
SOLIDITA' COLORI ALLO SFREGAMENTO A SECCO COLOUR FASTNESS TO DRY RUBBING			5	UNI EN ISO 105-X12
SOLIDITA' COLORI ALLO SFREGAMENTO A UMIDO COLOUR FASTNESS TO WET RUBBING			5	UNI EN ISO 105-x12
RESISTENTE RAGGI UV / HIGH UV RESISTANCE				
				
IDROREPELLENTE SU RICHIESTA / WATER REPELLENT ON REQUEST				
				
ON REQUEST				
TRATTAMENTO ANTIVIRALE SU RICHIESTA / ANTIVIRAL TREATMENT ON REQUEST				
				
ON REQUEST				

SUPREMASEA®

Sede legale e produttiva
Via Tonino da Lumezzane SNC
24057 Martinengo (BG) - Italy
Tel: **+39035844009**

SUPREMASEA®
DUBAI

48 Burj Gate, 10th Floor, room
#1001
Downtown, Dubai (EAU)
Tel: **+97143216260**

www.supremasea.it

info@naster.it

nastersrl@pec.it

P.IVA 00954820163